

A2 - Hummingbird Automatic Dispenser



- ➡ Minimum Shot: 1/2000Y
- ➡ 100% Recirculation
- ➡ Suitable for Sample Paint Dispensing

SANTINT • CHINA

Add: Feilong Road, Xingyang,
Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND

Add: Lageweg 35 - J, 2222 AG
Katwijk The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 19 Postępu Street
(warehouse no. 5)02-676
Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av. Rosa Kasinski,
1109, G29 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vehele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

A₂ - Hummingbird FEATURES >>>

SANTINT
WHERE INNOVATION MEETS PRECISION



Bluetooth/Wireless Module(Optional)

1 Patented Double Pump Double Nozzle

1/2000Y(0.015ml)
Minimum Shot



2 100% Recirculation

Zero nozzle dryness/blockage;
purge-free;
maintenance-free;
colorant saving;
stable accuracy.



3 Box/Table Tinting

Saving PC cost;
pre-installed software,
shorter installation time.



4 Calibration-free Piston Pump



<p></p> <p>P1.1 Piston Pump Sequential Dispensing</p>	<ul style="list-style-type: none"> Flow Rate 600ml/min Efficiency 200ml/min
<ul style="list-style-type: none"> Minimum Shot 1/2000Y(0.015ml) 	<ul style="list-style-type: none"> Pump Capacity 60ml Stirring Speed 20rpm
<ul style="list-style-type: none"> Canister Size 1.8L / 2.3L POM 2.3L / 3.8L Stainless Steel (Optional) NO. of Canisters Up to 16 	
<ul style="list-style-type: none"> Max Can Size (D X H) 320X600mm Machine Dimension (W X D X H) 707X848X1300mm Packing Dimension (W X D X H) 830X990X1500mm 	<ul style="list-style-type: none"> Loading Quantity 14 Pieces/20GP
<ul style="list-style-type: none"> Net Weight 130kg Gross Weight 155kg 	<ul style="list-style-type: none"> Power ≤ 100W Power Supply 220V/110V 50Hz/60Hz

A₂ - Hummingbird Technical Parameters

