

A3

Automatic
Dispenser



- ➔ High Efficiency
- ➔ High Accuracy
- ➔ Purge Free
- ➔ Freight Reduced 60%

● A3 Appearance

SANTINT • CHINA

Add: Sangong & Xingyun Road,
Xinyang City, Zhengzhou City,
Henan Province, 450121 China
Email: info@santint.com

SANTINT • HOLLAND

Add: Gieterij 28, 2211 XK
Noordwijkerhout, The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 43 Szyszkowa Street,
02-285 Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com


SANTINT • BRAZIL

Add: Av.Rosa Kasinski, 1109,
G11 e 12 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vehele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

A3 FEATURES >>>



■ take out cleaning box easily



● A3 Hummingbird Appearance
(Including dripping catcher)

1 High Efficiency

Efficiency up to 300ml/min.



2 Freight Reduced 60%

3 layers in container.
20GP contains 48 units
40GP contains 102 units




3 Double Pump Double Nozzle (A3 Hummingbird)

1/3000Y(0.01ml)
Minimum Shot.



4 Suitable for Z-VOC Colorant

100% recirculation
technology.
Timed recirculation
makes the colorant
noncondensing and
prevents the nozzle
from dryness and
blockage & colorant
from deterioration.



P1.1 Piston Pump
Sequential Dispensing

■ Single Pump Standard Flow Rate: 900 ml/min

■ Single Pump Standard Efficiency: 300ml/min
*It depends on the product property

■ Minimum Shot

A3: 1/384Y(0.077ml)

A3-Hummingbird: 1/3000Y(0.01ml)

*It depends on the product property

■ Pump Capacity

A3: 100ml

A3-Hummingbird: 90ml

■ Canister Volume: 2.3L

■ Stirring Speed: 20rpm

■ No. of Canisters: Up to 16

■ Can Size(DxH): 320x420mm(Max.)

■ Machine Size(WxDxH): 720x895x1220mm

■ Package Size(WxDxH): 990x765x770mm

■ Net Weight: 120kg

■ Rated Power: 100W

■ Gross Weight: 145kg

■ Power Supply: 220V/110V 50Hz/60Hz

A3



Technical Parameters

