

A4b-100%

Automatic Dispenser



- ➡ Efficiency Improved By 50%
- ➡ 100% Recirculation
- ➡ Box Tinting (Android)

● Electrical Can Table Version

SANTINT • CHINA

Add: Feilong Road, Xingyang,
Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND

Add: Lageweg 35 - J, 2222 AG
Katwijk The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 19 Postępu Street
(warehouse no. 5)02-676
Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av. Rosa Kasinski,
1109, G29 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vehele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com


A4b-100% FEATURES >>>



● Manual Can Table Version

1 100% Recirculation

Zero nozzle dryness/blockage;
purge-free;
maintenance-free;
colorant saving;
stable accuracy.



2 Box/Table Tinting

Saving PC cost;
pre-installed software,
shorter installation time.



3 High Accuracy

Minimum Shot 1/768Y
(0.039ml)




4 Calibration-free Piston Pump



5 Optional Hole Puncher

(Electrical lifting tray)



<p>P1 Piston Pump Sequential Dispensing</p>	<p>■ Flow Rate 900ml/min</p>
	<p>■ Efficiency 300ml/min</p>
<p>■ Minimum Shot 1/768Y(0.039ml)</p>	<p>■ Pump Capacity 100ml</p>
	<p>■ Stirring Speed 20rpm</p>
<p>■ Canister Size 1.8L / 2.3L / 6L POM 2.3L / 3.8L Stainless Steel (Optional)</p>	
<p>■ NO. of Canisters Up to 32</p>	
<p>■ Optional Electrical Can Table/Automatic Puncher</p>	
<p>■ Max Can Size (D X H) Manual 360X460mm Electrical 390X440mm</p>	
<p>■ Machine Dimension (W X D X H) 870X1026X1290mm</p>	
<p>■ Packing Dimension (W X D X H) 920X1170X1500mm</p>	
<p>Loading Quantity 12 Pieces/20GP</p>	
<p>■ Net Weight Electrical 245kg, Manual 215kg</p>	<p>■ Power ≤ 150W</p>
<p>■ Gross Weight Electrical 290kg, Manual 260kg</p>	<p>■ Power Supply 220V/110V 50Hz/60Hz</p>

A4b-100%

Technical Parameters

