

# A4b-HS

Automatic Dispenser



- ➡ High Efficiency:500ml/min
- ➡ High Accuracy:1/2000Y
- ➡ Suitable for Z-VOC colorant

**SANTINT • CHINA**

Add: Feilong Road, Xingyang,  
Zhengzhou, China  
Email: info@santint.com

**SANTINT • HOLLAND**

Add: Lageweg 35 - J, 2222 AG  
Katwijk The Netherlands  
Email: sales@santint-europe.com

**SANTINT • POLAND**

Add: 19 Postępu Street  
(warehouse no. 5)02-676  
Warsaw, Poland  
Email: albert@santintpoland.com

**SANTINT • U.S.A**

Add: 2000 Bloomingdale Road,  
Suite 205, Glendale Heights,  
IL 60139, U.S.A  
Email: info@santintusa.com

**SANTINT • BRAZIL**

Add: Av.Rosa Kasinski,  
1109, G29 Capuava,Mauá,  
SP - Brasil CEP 09380-128  
Email: marcos@santint.com

**SANTINT • INDIA**

Add: H.No.692, Gala No.04, Print  
World Industrial Complex,  
Bhatale, Vehele Village, Opposite  
Balaji Compound, Bhiwandi,  
Maharashtra – 421302  
Email: nick@santint.com

# A4b-HS FEATURES



## 1 Patented Double Pump Double Nozzle

Super High Accuracy:  
1/2000Y(0.015ml)  
Suitable for Sample  
Paint Dispensing



## 2 100% recirculation

Zero nozzle  
dryness/blockage;  
Purge-free;  
Maintenance-free;  
Colorant saving;  
Stable accuracy;  
Suitable for Z-VOC  
colorant.



## 3 Ergonomical filling height

Suitable filling height makes easy operation.

## 4 Weight feedback function optional

Electronic scale real-time feedbacks  
dispensing amount. Accurate compensation  
can be achieved according to feedback value.  
It applies to industrial paint, ink, automotive  
paint, etc.



P1.1 Piston Pump  
Sequential Dispensing

■ Efficiency 500ml/min

■ Minimum Shot  
1/2000Y (0.015ml)

■ Pump Capacity 100ml

■ Stirring Speed 20-25rpm

■ Canister Size 2.3L /3.8L/6L

■ No. of Canisters Up to 24

■ Electrical Can Table (Optional)

■ Can Size (D X H) Max 320mmX450mm Min 80mmX100mm

■ Machine Dimension (W X D X H) 870 X 1026 X 1290mm

■ Packing Dimension (W X D X H) 1168 X 920 X 1500mm

■ 12 pcs/20GP

■ Net Weight Electrical 265kg, Manual 235kg

■ Gross Weight Electrical 325kg, Manual 285kg

■ Power Electrical 450W, Manual 350W

■ Power Supply 220V/110V 50Hz/60Hz

# A4b-HS

## Technical Parameters

