

A5

Automatic Dispenser



- ➡ 1L/min High Efficiency
Suitable for Batch
Dispensing
- ➡ 1/2000Y Minimum Shot
Suitable for Sample
Paint Dispensing
- ➡ 100% Recirculation
Suitable for Z-VOC
Colorant

● Electrical can table

SANTINT • CHINA

Add: Sangong & Xingyun Road,
Xinyang City, Zhengzhou City,
Henan Province, 450121 China
Email: info@santint.com

SANTINT • HOLLAND

Add: Gieterij 28, 2211 XK
Noordwijkerhout, The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 43 Szyszkowa Street,
02-285 Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av. Rosa Kasinski, 1109,
G11 e 12 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vehele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

A5 Main Features >>>

SANTINT
WHERE INNOVATION MEETS PRECISION



1 Reduces Customer Waiting Time

High efficiency piston pump shortens tinting time.




2 Suitable for Sample Paint Dispensing

High accuracy Small pump & small nozzle, suitable for sample paint dispensing



3 Suitable for Z-VOC Colorant

100% recirculation technology. Timed recirculation makes the colorant noncondensing and prevents the nozzle from dryness and blockage & colorant from deterioration.



4 LCD Timely Displays Machine Status

5 Weight Feedback Function Optional

Electronic scale real-time feedbacks dispensing amount. Accurate compensation can be achieved according to feedback value. It applies to industrial paint, ink, automotive paint, etc.

■ Canister Configuration

16 Canisters: 4x6L+12x2.3L
24 Canisters: 24x2.3L(Stainless Steel)

- Pump Configuration: Sequential Piston pump
- Single Pump Standard Efficiency: 1L/min *It depends on the product property
- Minimum Shot: 1/2000Y(0.015ml) *It depends on the product property

- Applicable Can: Diameters≤350mm, Heights≤420mm
- Can Table: Manual, Electrical Optional
- Mixing Speed: 20-25r/min

- Machine Dimension(WxDxH): 830x895x1295mm
- Package Dimension(WxDxH): 900x1070x1480mm

- Net Weight: 240kg(Electrical) 220kg(Manual)
- Gross Weight: 300kg(Electrical) 280kg(Manual)

- Power Supply: 220V/110V 50Hz/60Hz
- Rated Power: 450W

A5

Technical Parameters

