

A7

Automatic Dispenser



- ➡ 1L/min High Efficiency Suitable for Batch Dispensing
- ➡ 1/2000Y Minimum Shot Suitable for Sample Paint Dispensing
- ➡ 100% Recirculation Suitable for Z-VOC Colorant

● Electrical Can Table

SANTINT • CHINA

Add: Sangong & Xingyun Road,
Xingyang City, Zhengzhou City,
Henan Province, 450121 China
Email: info@santint.com

SANTINT • HOLLAND

Add: Gieterij 28, 2211 XK
Noordwijkerhout, The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 43 Szyszkowa Street,
02-285 Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av. Rosa Kasinski, 1109,
G11 e 12 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vhele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

A7 Main Features >>>

SANTINT
WHERE INNOVATION MEETS PRECISION



1 Preferred Option for Medium/High Volume Locations

High efficiency piston pump shortens tinting time.




2 Suitable for Sample Paint Dispensing

High accuracy Small pump & small nozzle, suitable for sample paint dispensing



3 Suitable for Z-VOC Colorant

100% recirculation technology. Timed recirculation makes the colorant noncondensing and prevents the nozzle from dryness and blockage & colorant from deterioration.



4 LCD Timely Displays Machine Status

5 Weight Feedback Function Optional

Electronic scale real-time feedbacks dispensing amount. Accurate compensation can be achieved according to feedback value. It applies to industrial paint, ink, automotive paint, etc.

■ Canister Configuration

16 Canisters: 4x12L+12x6L
24 Canisters: 18x6L+6x2.3L
32 Canisters: 8x6L+24x2.3L
36 Canisters: 9x6L+27x2.3L

- Pump Configuration: Sequential piston pump
- Single Pump Standard Efficiency: 1L/min *It depends on the product property
- Minimum Shot: 1/2000Y(0.015ml) *It depends on the product property

- Applicable Can: Diameter≤490mm Height≤420mm
- Can Table: Electrical
- Mixing Speed: 20-25r/min

- Machine Dimension(WxDxH): 1100x1270x1325mm
- Package Dimension(WxDxH): 1150x1400x1400mm
8 pcs/20GP 16 pcs/40GP

- Net Weight: 350kg
- Gross Weight: 450kg

- Power Supply: 220V/110V 50Hz/60Hz
- Rated Power: 450W

A7

Technical Parameters

