

AH1000

Automatic Dispenser



Net Efficiency : 1000ml/minX5

Minimum Shot : 1/1024Y (Yellow Oxide Included)

Repeatability : ★ ★ ★ ★ ★ (1/768Y)

★ ★ ★ ★ ☆ (1/1024Y)

Durability : Yellow Oxide >10000L ; Others >20000L



SANTINT • CHINA

Add: Feilong Road, Xingyang,
Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND

Add: Lageweg 35 - J, 2222 AG
Katwijk The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 19 Postępu Street
(warehouse no. 5)02-676
Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av.Rosa Kasinski,
1109, G29 Capuava,Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vehale Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra – 421302
Email: nick@santint.com

AH1000

Automatic Dispenser


FEATURES >>>



1


Self-calibration

P6 pump starts from zero position for each dispensing.




2

Blockage Warning No Tube Explosion



3


Recirculation



4

Water Circulation Humidifier


Minimizing nozzle blockage



5

Three-Way Valve

Valve
temporary blocker
Air Exhauster



6

Multi-functional Roller Conveyor (Optional)



- Dispensing Type: Simultaneous
- Minimum Shot: 1/1024Y(0.029ml)
- Net Efficiency: 1000ml/minX5

- NO. of Canisters: Up to 32
- Canister Size: 6L/12L/22/50/200L
- Canister Material: POM、Stainless Steel (Optional)

- Can Table: Automatic
- Recirculation: Every 4 Hours
- Humidifier: Yes

- Stirring: 1 min/ h ■ Stirring Speed: 15r/min
- Laser Positioning: Yes
- timed stirring and timed recirculation's time interval customizable

- Dimension: 1690X1210X1320(mm)
(WDXH)

- Power: 400W
- Power Supply: 220V/110V 50Hz/60Hz

<<< **AH1000**
Technical Parameters

