

ES-7000

Paint Scale



- ➡ High Accurate Core
- ➡ Rechargeable Battery
- ➡ Gradienter Equipped

SANTINT • CHINA

Add: Feilong Road, Xingyang,
Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND

Add: Lageweg 35 - J, 2222 AG
Katwijk The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 19 Postępu Street
(warehouse no. 5) 02-676
Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av. Rosa Kasinski,
1109, G29 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vehale Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

ES-7000 FEATURES >>>

SANTINT
WHERE INNOVATION MEETS PRECISION



1 Easy Operation



2 Adjustable Displaying Angle

3 Big Screen


High accuracy with white backlight.



4 Built-in Rechargeable Battery

Suitable for various locations.

5 Stainless Steel Weighing Pan



- | | |
|--|-------------------------------------|
| ■ Maximum Capacity 7000 g | ■ Readability 0.1 g |
| ■ Accuracy Level III | ■ Unit kg g |
| ■ Displayer LCD with white backlight | |
| ■ Displaying Steady Time 1.2 Seconds | |
| ■ RS-232 Interface PC/Receipt Printer/Label Printer | |
| ■ Height 370 mm | ■ Weighing Pan Size Diameter 230 mm |
| ■ Material Scale Body: Cast Aluminium Weighing Pan: Stainless Steel | |
| ■ Maximum Safety Capacity ≤150% ■ User may self-define some parameters | |
| ■ Power Supply AC Adapter (12 V 500 mA) Built-in rechargeable battery (6 V 4 AH) | |
| ■ Weight 2.65 kg | ■ Ambient Temperature 5~35 °C |
| ■ Packing Size 350×390×510 mm | ■ Relative Humidity 20-80% RH |

ES-7000

Technical Parameters

